

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



10/8/0, 164
PTO-892


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G06F 12/02	A1	(11) International Publication Number: WO 00/60468 (43) International Publication Date: 12 October 2000 (12.10.00)
<p>(21) International Application Number: PCT/EP00/01959</p> <p>(22) International Filing Date: 7 March 2000 (07.03.00)</p> <p>(30) Priority Data: 9907278.7 31 March 1999 (31.03.99) GB</p> <p>(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).</p> <p>(72) Inventor: HOULDSWORTH, Richard, J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).</p> <p>(74) Agent: WHITE, Andrew, G.; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).</p>	<p>(81) Designated States: JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, Pt, SE).</p> <p>Published <i>With international search report.</i></p>	

(54) Title: **MEMORY RECLAMATION METHOD AND APPARATUS**

(57) Abstract

A method and apparatus for reclaiming memory space allocated to data structures comprising data objects linked by identifying pointers. The memory allocated to data objects is reclaimed using two systems. In the first system (240), the data structures are traversed to identify those objects to which no references are made by the pointers of other objects, and the memory allocated to those objects to which no references are made is reclaimed. In the second system (210), objects which are not descendants of root objects are determined and the memory allocated to those objects is reclaimed. Cycles of the first system are interleaved with cycles of the second system.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MEMORY RECLAMATION METHOD AND APPARATUS

The present invention relates to a memory reclamation method and
5 apparatus and in particular, though not exclusively, to such method and
apparatus in which repeated sweeps of memory using alternative algorithms
are made.

10 Garbage collection is the automated reclamation of system memory
space after its last use by a programme. A number of examples of garbage
collecting techniques are discussed in "Garbage Collection- Algorithms for
Automatic Dynamic Memory Management" by R. Jones et al, pub. John Wiley
& Sons 1996, ISBN 0-471-94148-4, at pages 1 to 18, and "Uniprocessor
15 Garbage Collection Techniques" by P.R. Wilson, Proceedings of the 1992
International Workshop on Memory Management, St. Malo, France,
September 1992. Whilst the storage requirements of many computer programs
are simple and predictable, with memory allocation and recovery being
handled by the programmer or a compiler, there is a trend toward functional
20 languages having more complex patterns of execution such that the lifetimes
of particular data structures can no longer be determined prior to run-time and
hence automated reclamation of this storage, as the program runs, is
essential.

A common feature of a number of garbage collection reclamation
25 techniques, as described in the above-mentioned Wilson reference, is
incrementally traversing the data structure formed by referencing pointers
carried by separately stored data objects. The technique involves first marking
all stored objects that are still reachable by other stored objects or from
external locations by tracing a path or paths through the pointers linking data
30 objects.

This may be followed by sweeping or compacting the memory - that is to say examining every object stored in the memory to determine the unmarked objects whose space may then be reclaimed.

Each garbage collection algorithm has its own particular strengths and weaknesses. For example a mark-sweep garbage collector is able to detect all unused objects and reclaim the memory occupied by them in a single mark-sweep pass through the memory heap. However, garbage cannot be identified for certain until all used objects have been marked. In contrast, a reference counting garbage collector is able to detect unused objects and immediately reclaim memory occupied by them. Unfortunately, reference counting cannot, by itself, identify unused circular loops of objects, where the tail of a list is linked to the head.

Furthermore, some garbage collected languages and environments such as Java (@Sun Microsystems Inc.), Modula-3 and Cedar support the concept of finalisation, which it is necessary that garbage collection algorithms cater for. Stored data objects created by a program process may have an associated finaliser procedure which is to be executed after the object is detected as unmarked and nominally becomes available for garbage collection but before the memory occupied by the data object is reclaimed. The purpose of this feature is to allow an object to clean up any other system resources the object has claimed before it is destroyed. For example, the finaliser for a Java File Object would close all the system file handles held by the object.

However, a finaliser is just a special type of procedure associated with an object with all the power of the programming language available to it. The finaliser procedure can therefore access and manipulate all data objects accessible from the object being finalised. Therefore, all objects accessible by a finaliser, such as descendant objects accessible from referencing pointers held by the data object, must be explicitly excluded from garbage collection. Furthermore, it is possible for the finaliser method to resurrect any such objects accessible by a finaliser, including the object being finalised itself, by making the object accessible to the program process again. Consequently, a garbage collection procedure cannot delete any objects that are accessible by

a finalisable object until its finaliser has executed and the accessibility of the objects has been re-evaluated. In Java and other languages, the possibility of an object repeatedly resurrecting itself is typically removed by stating that the finaliser for each instance is executed only once. This control on finalisation
5 will be assumed herein.

In PC's or workstations, the extra processing and memory load to support finalisation is not usually a problem due to the amount of memory typically available in a PC, although the support will, of course, affect the overall efficiency. In low-memory environments such as set-top boxes,
10 however, support for finalisers can cause problems and even a concurrent or incremental garbage collector may have to halt the program until it has executed some or all of the outstanding finalisers and reclaimed any memory used by them.

15 According to a first aspect of the present invention, there is provided a method of reclaiming memory space allocated to data structures comprising data objects linked by identifying pointers, in which the memory allocated to data objects is reclaimed using two systems: a first system, by which the data
20 structure is traversed to identify those objects to which no references are made by the pointers of other objects, and reclaiming the memory allocated to those objects to which no references are made; and a second system, which determines which objects are not descendants of root objects and reclaiming the memory allocated to those objects, wherein cycles of the first system are
25 interleaved with cycles of the second system.

The second system may determine which objects are descendants of root objects from a mark associated with each object, which mark has been set by the first system if the object is a descendant of a root object.

An advantage of the present invention is that one traversal of the heap
30 gives information required for memory reclamation using both systems.

The cycles of the first system may reclaim the memory allocated to a group of data objects the pointers of which reference each other but none of which are referred to by the pointer of a root object.

The interleaving of first and second systems may be performed according to predetermined criteria including: cycles of the first system may be performed until no unreferenced objects are found, followed by a cycle of the second system; a cycle of the first system may be interleaved between cycles of the second system; a first number of cycles of the first system are interleaved between a second number of cycles of the second system. A global indicator may dictate from which system the next memory reclamation cycle will be derived.

The memory space may be traversed in a first direction during even numbered cycles and traversed in a second, alternate, direction during odd numbered cycles. A first mark may be associated with objects referenced by pointers of other objects found during the traversal in the first direction. A second mark may be associated with objects referenced by pointers of other objects found during the traversal in the second direction. An object found to be unreferenced by pointers of other objects traversed in one direction and not having the mark from a prior traversal in the alternate direction may be deleted.

Changes to pointers referencing objects may be monitored and the first system may only traverse a data structure to identify those objects to which no references are made by the pointers of other objects when a change to a pointer referencing a constituent object of the data structure occurs. If a change to a pointer which uniquely references an object occurs, the uniquely referenced object may be immediately deleted.

According to another aspect of the present invention, there is provided a data processing apparatus comprising a data processor coupled with a random access memory containing data structures comprising data objects linked by identifying pointers, the processor being configured to provide the following for operating on the stored plurality of data objects: first means for traversing the data structures to identify those objects to which no references

are made by the pointers of other objects, and for reclaiming the memory allocated to those objects to which no references are made; and second means for determining which objects are not descendants of root objects and for reclaiming the memory allocated to those objects, wherein cycles of the first
5 means are interleaved with cycles of the second means.

In the present invention, repeated sweeps of heap memory are performed using alternating complementary garbage collection methods to improve the efficiency of garbage collection, utilising the benefits of each method whilst avoiding their inherent weaknesses. Advantageously, the
10 garbage collection method of the present invention identifies finaliser-accessible objects.

More advantageously, finalisable objects identified are topologically ordered and executed to avoid having to repeatedly process a finalisable object and its descendants which are descendants of another finalisable
15 object.

Furthermore, the method of the present invention is composed of a number of simple steps, thereby permitting fine-grained incremental implementations of the garbage collector.

20

The present invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a block diagram of a data processing system suitable to embody the present invention;

25 Figure 2 is a flow chart of the method of the present invention;

Figure 3 is a flow chart of selected steps of the method of the present invention shown in more detail;

Figure 4 is a flow chart of other selected steps of the method of the present invention shown in more detail; and

30 Figures 5 to 10 are block diagrams representing the processing of data structures according to the method of the present invention.

Figure 1 represents a data processing system, such as a personal computer, which acts as host for a number of software utilities which may, for example, configure the system as a browser for data defining a virtual environment. The system comprises a central processing unit (CPU) 10 coupled via an address and data bus 12 to random-access (RAM) and read-only (ROM) memories 14, 16. These memories may be comprised of one or several integrated circuit devices and may be augmented by a system hard-disk as well as means to read from additional (removable) memory devices, such as a CD-ROM. Also coupled to the CPU 10 via bus 12 are first and second user input devices 18, 20 which may suitably comprise a keyboard and a cursor control and selection device such as a mouse or trackball. Audio output from the system is via one or more speakers 22 driven by an audio processing stage 24. Video output from the system is presented on display screen 26 driven by display driver stage 28 under control of the CPU 10. A further source of data for the system is via on-line link to remote sites, for example via the Internet, to which end the system is provided with a network interface 30 coupled to the bus 12.

The present invention is particularly embodied in memory management for a working area of the RAM 14 under control of the CPU 10; a controlling program for this may initially be held in ROM 16 and loaded up with the operating system on power-up. The following examples are compliant with concurrent garbage collection and memory management techniques in the Java (® Sun Microsystems Inc) virtual machine and the terminology should be construed accordingly: it will be recognised however that the present invention is not restricted to Java-compliant systems, to concurrent (or incremental) garbage collection, nor to purely virtual memory management.

Figure 2 is a flow chart of a memory reclamation method according to the present invention. The method has two alternately run sweeping systems operating on a memory heap in a continuous loop. The first system performs a mark-sweep for detecting and reclaiming memory from unused circular referenced objects (such as a list where the tail is arranged to point at the

head). The second system performs a reference-sweep for detecting and reclaiming memory from objects that are not descendants of root objects accessible by programs. A global variable Marking is used to control which of the two systems should be executed next. Each object has a number of status fields, as shown in the following table;

Field	Possible States
Reference	Unreffed - No references to object found Reffed - One or more references to object found
Mark	Unmarked - Object has not held a mark token in this cycle Mark - Object currently holds a mark token Marked - Object has previously held a mark token in this cycle
Finaliser	Finalisable - Object has an unexecuted finaliser Finalised - Object has an executed finaliser No_Finaliser - Object has no finaliser
Root	True - Object is permanent & should never be deleted False - Object is not permanent

A newly created object is set Reference=Reffed and Mark=Marked. The settings of status fields Finaliser and Root will depend on the object.

On starting, Marking is set to false in step 200. The continuous loop is then entered which repeats the following steps; if Marking is false, a mark-sweep is performed in step 210 and Marking is then set to True in step 220, otherwise, Marking is set to false in step 230 and a reference-sweep is performed in step 240.

Figure 3 is a flow chart of the mark-sweep performed in step 210. Each object in the heap is checked to determine if its Mark field is set to Unmarked in step 300. If so, its Finaliser field is checked in step 310. Finalisable objects have their Finalisers executed in step 320 and are set to Finalised, Reffed and Marked in step 330. The memory allocated to all other unmarked objects is reclaimed in step 340. If an object is not Unmarked, a root object has the Mark field set to Mark in step 350 whilst non-root objects have the Mark field set to Unmarked in step 360.

Figure 4 is a flow chart of the reference-sweep performed in step 240. Each object in the heap is checked to determine if its Reference field is set to Unreffed in step 400. If so, its Finaliser field is checked in step 410. Finalisable objects have their Finalisers executed in step 420 and are set to Finalised, Reffed and Marked in step 430. The memory allocated to all other unmarked objects is reclaimed in step 440. If an object is not Unreffed, a non-root object has its Reference field set to Unreffed in step 450. Steps 460-480 are then performed on each object referenced by the object currently being processed. In step 460, the Reference field of the object referenced is set to Reffed. If the Mark field of the referring object is set to Mark and the Mark field of the object referenced is set to Unmarked, the Mark field of the object referenced is set to Mark in step 470 and the global variable Marking is set to true in step 480. If the Mark field of the object being processed is set to Mark, this is changed to Marked in step 490.

Figures 5 to 10 show the processing of data structures comprising a number of data objects according to the method of Figures 2 to 4. Figure 5 shows data structures 500, 510, 520, 530 and 540 in their initial states (Marked and Reffed).

Figure 6 shows the data structures after the mark-sweep cycle of the system. The mark state of objects 500, 530 and 540 is changed to Unmarked. As they are root objects, the mark state of data objects 510a and 520 is changed to Mark. The mark state of the remaining objects 510b-510e is changed to Unmarked.

Figure 7 shows the data structures after the reference-sweep cycle of the system. The reference state of data object 500a-500c is changed to Unreffed (step 450) and then back to Reffed (step 460) again as each data object is referenced in the circular loop. The referenced state of data objects 510b-510e is changed to Unreffed and the mark state of data objects 510a-510e is changed from Unmarked, through Mark, to Marked as the Mark token propagates down the tree 510. This propagation could take more than one reference-sweep, depending on the ordering of data object 510a-510e in memory. The changing of mark status also changes the global variable Marking to true. Data object 520 is Marked and Reffed as it is a root data object. The state of data objects 530a and 540 is changed to Unreffed and Unmarked as neither are linked to a root data object and therefore must be garbage.

As Marking was set to true, another reference-sweep is performed in Figure 8. Again, the reference state of data object 500a-500c is changed to Unreffed and then back to Reffed again as each data object is referenced in the circular loop. The state of data objects 510a-510e and 520 is unchanged after this sweep. Data object 540 is detected as Unmarked and, as it has no finaliser, the memory allocated to the data object is reclaimed. Data object 530 is also detected as Unmarked. However, the object 530a has a finaliser which is therefore executed and the status of the object is set to Marked, Reffed and Finalised. Due to the Reffed setting, object 530a and 530b are not reclaimed during this cycle.

The next cycle is a mark-sweep. The status of the data structures after this is shown in Figure 9. As none of the data objects 500a-500c are marked, they are reclaimed. The marking status of data objects 510a and 520 is reset to Mark and the marking status of data object 510b-510e and 530a is set to Unmarked. Data object 530b is reclaimed as it is Unmarked.

During the reference-sweep cycle shown in Figure 10, data object 530a is reclaimed.

As an alternative to immediately running the finaliser of a finalisable object, thereby making it safe to be reclaimed immediately afterwards, it may

be preferable to queue the execution of finalisers. In order to prevent finalisable objects and their descendants from being reclaimed, the finalisable object could be made a root object for the duration of the queuing and execution of the finaliser.

5 In order to improve the efficiency of the method of the present invention when processing long lists of linked data objects, the direction of the sweep cycles through the heap could be alternated. Two further reference bits '<' and '>' would be maintained for each data object. The bits represent a reference count of references from each direction in the heap. The '<' bit is marked on a sweep up the heap and the '>' is marked on the sweep down the heap that
10 subsequently follows. An object may be safely reclaimed immediately if both '<' and '>' are not set. This is because when an object is reached by the sweep, references from that direction must have been checked. The count from the other direction was obtained on the previous sweep, and likewise for any
15 references from that side of the heap. Therefore there can be no other references and the object can be reclaimed. In the worst case, a list where elements are totally interleaved would still be reclaimed in half as many cycles as a unidirectional sweep.

Whilst the in above description reference counting is performed during
20 the reference-sweep cycle, the reference counting could alternatively, or in addition, be performed during the mark-sweep cycle. This would mean in the above example that objects 540 and 530a are reclaimed one cycle earlier.

It has been assumed during this description that a mark state is propagated through a data structure in a single cycle. However, the method
25 and apparatus of the present invention are equally applicable to situations where a mark is propagated through a data structure during a number of cycles.

Repetitive Unreffed-Reffed transitions, such as in the above illustrated case of the cyclic list data structure 500, could be avoided by extending the
30 write barrier (normally used to prevent a program process changing a reference due to be followed in the sweep) so that changes to objects between sweeps are noted. Objects would remain in the Reffed state unless a change

to the object occurs. An object goes into the 'Changed' state when a reference to the object is altered. The 'Changed' state can be regarded as an intermediate reference state. On a reference sweep, an object with the 'Changed' state is modified to Unreffed.

- 5 To reduce the number of reference sweeps needed to recycle memory, the reference state could be extended to include;

State	
Unreffed	Reference count = 0
Unique	Reference count = 1
Shared	Reference count ≥ 1
Changed	Reference count = unknown

- 10 The write barrier must now be extended to include the transition from Shared to Changed states when a reference to the object is deleted, and the transition from Unique to Unreffed states when the reference to uniquely accessed data is lost. The data object can be deleted during the write barrier operation, without having to wait for the next sweep to pass.

- 15 The number of reference sweeps needed to conclude a mark trace is equal to the maximum span from a root to a live item of data. For structures such as linked lists, this span length is likely to be very long. An adaptive approach could allow a deeper trace down through objects when the amount of work performed on each sweep is low. The number of mark token propagation operations on the previous sweep could be used as a factor to
20 estimate the depth of scanning to perform on this sweep.

From reading the present disclosure, other modifications will be apparent to persons skilled in the art. Such modifications may involve other features which are already known in the design, manufacture and use of data processing and/or data network access apparatus and devices and component
5 parts thereof and which may be used instead of or in addition to features already described herein.

CLAIMS

1. A method of reclaiming memory space allocated to data structures comprising data objects linked by identifying pointers, in which the memory allocated to data objects is reclaimed using two systems:
5 a first system, by which the data structures are traversed to identify those objects to which no references are made by the pointers of other objects, and reclaiming the memory allocated to those objects to which no references are made; and
10 a second system, which determines which objects are not descendants of root objects and reclaiming the memory allocated to those objects, wherein cycles of the first system are interleaved with cycles of the second system.
- 15 2. A method as claimed in claim 1, wherein the second system determines which objects are descendants of root objects from a mark associated with each object, which mark has been set by the first system if the object is a descendant of a root object.
- 20 3. A method as claimed in claim 1 or 2, wherein the interleaving of first and second systems is performed according to predetermined criteria.
4. A method as claimed in claim 3, wherein the predetermined criteria perform cycles of the first system until no unreferenced objects are
25 found, followed by a cycle of the second system.
5. A method as claimed in claim 3, wherein one or several cycles of the first system are interleaved between one or several cycles of the second system.

6. A data processing apparatus comprising a data processor coupled with a random access memory containing data structures comprising data objects linked by identifying pointers, the processor being configured to provide the following for operating on the stored plurality of data objects: first means for traversing the data structures to identify those objects to which no references are made by the pointers of other objects, and for reclaiming the memory allocated to those objects to which no references are made; and second means for determining which objects are not descendants of root objects and for reclaiming the memory allocated to those objects, wherein cycles of the first means are interleaved with cycles of the second means.

7. A data processing apparatus as claimed in claim 6, wherein the second means determines which objects are descendants of root objects from a mark associated with each object, which mark has been set by the first system if the object is a descendant of a root object.

8. A data processing apparatus as claimed in claims 6 or 7, wherein the memory space is traversed in a first direction during even numbered cycles and is traversed in a second, alternate, direction during odd numbered cycles.

9. A data processing apparatus as claimed in claim 8, comprising means for associating a first mark with objects referenced by pointers of other objects found during the traversal in the first direction.

10. A data processing apparatus as claimed in claim 9, comprising means for associating a second mark with objects referenced by pointers of other objects found during the traversal in the second direction.

11. A data processing apparatus as claimed in claim 10, further comprising means for deleting an object found to be unreferenced by pointers of other objects traversed in one direction and not having the mark from a prior traversal in the alternate direction.

5

12. A data processing apparatus as claimed in any one of claims 6 to 11, comprising means for monitoring changes to pointers referencing objects, wherein the first means only traverses a data structure to identify those objects to which no references are made by the pointers of other objects when a
10 change to a pointer referencing a constituent object of the data structure occurs.

13. A data processing apparatus as claimed in claim 12, comprising means for deleting a uniquely referenced object if a change to a pointer which
15 uniquely references the object occurs.

14. A program storage device readable by a machine and encoding one or more programs of instructions for executing the method steps of a specified one of claims 1 through 5.

1/8




FIG. 1

2/8




FIG. 2

3/8




FIG. 3

4/8




FIG. 4A

5/8




FIG. 4B

6/8




FIG. 5




FIG. 6

7/8




FIG. 7




FIG. 8

8/8




FIG. 9




FIG. 10

INTERNATIONAL SEARCH REPORT

Intern. Appl. No.

PCT/EP 00/01959

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06F12/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>ATKINS M C ET AL: "THE ACTIVE DEALLOCATION OF OBJECTS IN OBJECT-ORIENTED SYSTEMS"</p> <p>SOFTWARE PRACTICE & EXPERIENCE, GB, JOHN WILEY & SONS LTD. CHICHESTER, vol. 18, no. 11, 1 November 1988 (1988-11-01), pages 1073-1089, XP000110495</p> <p>ISSN: 0038-0644</p> <p>page 1078, line 21 -page 1080, line 21</p> <p style="text-align: center;">-/-</p>	1,6

☒ Further documents are listed in the continuation of box C.

☐ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

14 July 2000

Date of mailing of the international search report

24/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nielsen, O

INTERNATIONAL SEARCH REPORT

Intern. Appl. No.

PCT/EP 00/01959

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>CORPORAAL H ET AL: "THE DESIGN SPACE OF GARBAGE COLLECTION" PROCEEDINGS OF THE ANNUAL EUROPEAN COMPUTER CONFERENCE. (COMPEURO),US,LOS ALAMITOS, IEEE. COMP. SOC. PRESS, vol. CONF. 5, 13 May 1991 (1991-05-13), pages 423-428, XP000245658 the whole document</p>	1,6